


Features:




- Exceptional conducted attenuation performance
- Excellent thermal stability
- Standard or wide mounting flange
- Designed with C14 and C20 connector
- Custom versions available on request

Applications:

- Power Systems
- Electronic Equipment
- Frequency convertors
- Stepper motor drives
- Rack mounting Equipment
- UPS/Inverters

DATASHEET
IEC INLET FILTER - MF 300 Series

These series range of filters with IEC Inlet are designed to suppress undesirable electrical disturbances in Power Lines. They limit the amplitude of interfering voltages on AC powerlines and prevent them from propagating into or out of the filtered equipment

Performance Indicator:

Rated Current (A):

Typical Circuit Diagram:



CY capacitors are not applicable for the medical version


Bleeder Resistor is optional


Technical Specifications:


Maximum Continuous Operating Voltage	: 250 VAC, 50/60Hz (UL Approval) 250 VDC
Operating Frequency	: DC to 400Hz
Current ratings	: 1A to 20A @40°C
High Potential test voltage	: L+N - G 2250VDC for 2 sec L-N 1450VDC for 2 sec
Overload Capability	: 135% of Rated current for 15 minutes
Design Corresponding to	: UL 60939-3, CSA 22.2 No.8-13 and IEC 60939 1&2
Flammability corresponding to	: UL 94 V-0
Temperature range	: -25°C to +100°C
Climatic Category	: 25/100/21


Ordering Information :


Standard Version : High Performance						
Model Number	Part Number	Current Rating @40°C(A)	Leakage Current @250 VAC/50Hz (mA)	Input Connector	Output Termination 	Min.Weight (g)
MF300-102-1-4	E100001-2	1	0.34	C14	-4	80
MF300-102-2-4	E100001-8	2	0.34	C14	-4	80
MF300-102-3-4	E100001-3	3	0.34	C14	-4	80
MF300-102-6-4	E100001-4	6	0.34	C14	-4	80
MF300-102-10-4	E100001-5	10	0.34	C14	-4	80
MF300-102-15-4	E100001-6	15	0.34	C14	-4	80
MF300-102-16-4	E113091-1	16	0.34	C20	-4	120
MF300-102-20-4	E113092-1	20	0.34	C20	-4	120
MF300-502-1-4	E113093-1	1	0.34	C14	-4	80
MF300-502-2-4	E113094-1	2	0.34	C14	-4	80
MF300-502-3-4	E113095-1	3	0.34	C14	-4	80
MF300-502-6-4	E113096-1	6	0.34	C14	-4	80
MF300-502-10-4	E113097-1	10	0.34	C14	-4	80
MF300-502-15-4	E113098-1	15	0.34	C14	-4	80
MF300-502-16-4	E113099-1	16	0.34	C20	-4	120
MF300-502-20-4	E113100-1	20	0.34	C20	-4	120

Safety Version : High Performance						
Model Number	Part Number	Current Rating @40°C(A)	Leakage Current @250 VAC/50Hz (mA)	Input Connector	Output Termination 	Min.Weight (g)
MF300-102S-1-4	E113111-1	1	0.16	C14	-4	80
MF300-102S-2-4	E113112-1	2	0.16	C14	-4	80
MF300-102S-3-4	E113113-1	3	0.16	C14	-4	80
MF300-102S-6-4	E113114-1	6	0.16	C14	-4	80
MF300-102S-10-4	E113115-1	10	0.16	C14	-4	80
MF300-102S-15-4	E113116-1	15	0.16	C14	-4	80
MF300-102S-16-4	E113117-1	16	0.16	C20	-4	120
MF300-102S-20-4	E113118-1	20	0.16	C20	-4	120
MF300-502S-1-4	E113119-1	1	0.16	C14	-4	80
MF300-502S-2-4	E113120-1	2	0.16	C14	-4	80
MF300-502S-3-4	E113121-1	3	0.16	C14	-4	80
MF300-502S-6-4	E113122-1	6	0.16	C14	-4	80
MF300-502S-10-4	E113123-1	10	0.16	C14	-4	80
MF300-502S-15-4	E113124-1	15	0.16	C14	-4	80
MF300-502S-16-4	E113125-1	16	0.16	C20	-4	120
MF300-502S-20-4	E113126-1	20	0.16	C20	-4	120

Medical Version : High Performance						
Model Number	Part Number	Current Rating @40°C(A)	Leakage Current @250 VAC/50Hz (µA)	Input Connector	Output Termination 	Min.Weight (g)
MF300-102M-1-4	E100998-2	1	0	C14	-4	80
MF300-102M-2-4	E100998-8	2	0	C14	-4	80
MF300-102M-3-4	E100998-3	3	0	C14	-4	80
MF300-102M-6-4	E100998-4	6	0	C14	-4	80
MF300-102M-10-4	E100998-5	10	0	C14	-4	80
MF300-102M-15-4	E100998-6	15	0	C14	-4	80
MF300-102M-16-4	E113101-1	16	0	C20	-4	120
MF300-102M-20-4	E113102-1	20	0	C20	-4	120
MF300-502M-1-4	E113103-1	1	0	C14	-4	80
MF300-502M-2-4	E113104-1	2	0	C14	-4	80
MF300-502M-3-4	E113105-1	3	0	C14	-4	80
MF300-502M-6-4	E113106-1	6	0	C14	-4	80
MF300-502M-10-4	E113107-1	10	0	C14	-4	80
MF300-502M-15-4	E113108-1	15	0	C14	-4	80
MF300-502M-16-4	E113109-1	16	0	C20	-4	120
MF300-502M-20-4	E113110-1	20	0	C20	-4	120

Standard Version : Very High Performance						
Model Number	Part Number	Current Rating @40°C(A)	Leakage Current @250 VAC/50Hz (mA)	Input Connector	Output Termination 	Min.Weight (g)
MF300-103-1-4	E113127-1	1	0.34	C14	-4	80
MF300-103-2-4	E113128-1	2	0.34	C14	-4	80
MF300-103-3-4	E113129-1	3	0.34	C14	-4	80
MF300-103-6-4	E113130-1	6	0.34	C14	-4	80
MF300-103-10-4	E113131-1	10	0.34	C14	-4	80
MF300-103-15-4	E113132-1	15	0.34	C14	-4	80
MF300-103-16-4	E113133-1	16	0.34	C20	-4	120
MF300-103-20-4	E113134-1	20	0.34	C20	-4	120
MF300-503-1-4	E113135-1	1	0.34	C14	-4	80
MF300-503-2-4	E113136-1	2	0.34	C14	-4	80
MF300-503-3-4	E113137-1	3	0.34	C14	-4	80
MF300-503-6-4	E113138-1	6	0.34	C14	-4	80
MF300-503-10-4	E113139-1	10	0.34	C14	-4	80
MF300-503-15-4	E113140-1	15	0.34	C14	-4	80
MF300-503-16-4	E113141-1	16	0.34	C20	-4	120
MF300-503-20-4	E113142-1	20	0.34	C20	-4	120


Safety Version : Very High Performance						
Model Number	Part Number	Current Rating @40°C(A)	Leakage Current @250 VAC/50Hz (mA)	Input Connector	Output Termination 	Min.Weight (g)
MF300-103S-1-4	E113159-1	1	0.16	C14	-4	80
MF300-103S-2-4	E113160-1	2	0.16	C14	-4	80
MF300-103S-3-4	E113161-1	3	0.16	C14	-4	80
MF300-103S-6-4	E113162-1	6	0.16	C14	-4	80
MF300-103S-10-4	E113163-1	10	0.16	C14	-4	80
MF300-103S-15-4	E113164-1	15	0.16	C14	-4	80
MF300-103S-16-4	E113165-1	16	0.16	C20	-4	120
MF300-103S-20-4	E113166-1	20	0.16	C20	-4	120
MF300-503S-1-4	E113167-1	1	0.16	C14	-4	80
MF300-503S-2-4	E113168-1	2	0.16	C14	-4	80
MF300-503S-3-4	E113169-1	3	0.16	C14	-4	80
MF300-503S-6-4	E113170-1	6	0.16	C14	-4	80
MF300-503S-10-4	E113171-1	10	0.16	C14	-4	80
MF300-503S-15-4	E113172-1	15	0.16	C14	-4	80
MF300-503S-16-4	E113173-1	16	0.16	C20	-4	120
MF300-503S-20-4	E113174-1	20	0.16	C20	-4	120

Medical Version : Very High Performance						
Model Number	Part Number	Current Rating @40°C(A)	Leakage Current @250 VAC/50Hz (µA)	Input Connector	Output Termination 	Min.Weight (g)
MF300-103M-1-4	E113143-1	1	0	C14	-4	80
MF300-103M-2-4	E113144-1	2	0	C14	-4	80
MF300-103M-3-4	E113145-1	3	0	C14	-4	80
MF300-103M-6-4	E113146-1	6	0	C14	-4	80
MF300-103M-10-4	E113147-1	10	0	C14	-4	80
MF300-103M-15-4	E113148-1	15	0	C14	-4	80
MF300-103M-16-4	E113149-1	16	0	C20	-4	120
MF300-103M-20-4	E113150-1	20	0	C20	-4	120
MF300-503M-1-4	E113151-1	1	0	C14	-4	80
MF300-503M-2-4	E113152-1	2	0	C14	-4	80
MF300-503M-3-4	E113153-1	3	0	C14	-4	80
MF300-503M-6-4	E113154-1	6	0	C14	-4	80
MF300-503M-10-4	E113155-1	10	0	C14	-4	80
MF300-503M-15-4	E113156-1	15	0	C14	-4	80
MF300-503M-16-4	E113157-1	16	0	C20	-4	120
MF300-503M-20-4	E113158-1	20	0	C20	-4	120

Note :

The EMI filter model name for MF 140 has been updated to MF300-XXXM-X-X.

Product Selector















Insertion Loss : High Performance





..... Common mode ——— Differential Mode

Per CISPR 17 C=50Ω/50Ω D=50Ω/50Ω



Standard Version




16A**20A****Safety Version****1A****2A****3A****6A**




Medical Version




3A




6A




10A




15A



16A















20A















Insertion Loss : Very High Performance

Standard Version




16A**20A****Safety Version****1A****2A****3A****6A**

10A**15A****16A****20A****Medical Version****1A****2A**


3A**6A****10A****15A****16A****20A**

Mechanical Drawing


Screw Mount 1A to 15A - C14 Connector




Screw Mount 16A & 20A - C20 Connector



Snap in Mount 1A to 15A - C14 Connector



Snap in Mount 16A & 20A - C20 Connector



Note: All dimensions in mm Tolerances according to ISO 2768-C